

# ***JOURNAL***

**LAJU PENYUMBATAN PIPA PADA *HEAT EXCHANGER*  
TIPE *SHELL AND TUBE* DAN PENGENDALIANNYA  
DENGAN ADITIF ASAM FORMAT DAN ASAM OKSALAT**



## ***JOURNAL TUGAS AKHIR***

**Disusun sebagai salah satu syarat  
untuk memperoleh gelar  
Sarjana S-1 pada Jurusan Teknik Mesin  
Fakultas Teknik  
Universitas Muhammadiyah Semarang**

**Disusun oleh:**

**Fajar Rozaqi  
NIM : C2A215014**

**FAKULTAS TEKNIK  
UNIVERSITAS MUHAMMADIYAH SEMARANG  
2018**

# Blockage Rate Pipe on Shell and Tube Heat Exchanger and Controlled with Formic Acid and Oxalic Acid Additives

W. Mangestiyono<sup>a)</sup>, S. Raharjo<sup>b)</sup>, A.W. Sejati<sup>b)</sup>, F. Rozaqi<sup>b)</sup>

<sup>a)</sup>Mechanical Engineering, School of Vocation, Diponegoro University, Semarang 50275, Indonesia

<sup>b)</sup>Mechanical Engineering, Muhammadiyah University, Semarang, Indonesia.

\*Corresponding author Email : rhombo\_hedral@yahoo.co.id

CaCO<sub>3</sub> fouling in Shell and Tube Heat Exchanger has been reported by several researchers that its existence declines heat transfer process until 30 times lower. Therefore, the current research was conducted to investigate the fouling resistant and addressed to minimize of investment cost. The method used in was categorized as chemical mitigation which antiscalant reagent i.e. formic acid (CH<sub>3</sub>O<sub>2</sub>) and oxalic acid (C<sub>2</sub>H<sub>2</sub>O<sub>4</sub>) was added to the solution.

**Keywords** : CaCO<sub>3</sub>, Heat Exchanger, formic acid, oxalic acid, crystal, morphology

## 1. Introduction

CaCO<sub>3</sub> fouling in Shell and Tube Heat Exchanger (STHE) has been known as the disturbance in heat transfer processes<sup>1</sup>. Several researchers reported that the exist of CaCO<sub>3</sub> fouling declines heat transfer process until 30 times lower<sup>2</sup> which the term usually called as fouling resistance<sup>3</sup>. When the phenomenon taken place, STHE design would not suitable to the system anymore as same as those that the design and capacity too smaller. To answer those fouling resistance problem, STHE designer marks up the capacity approximately one-third or 35% of the initially even though higher cost must be paid<sup>4</sup>. Therefore, the current research was conducted to investigate the fouling resistant and addressed to minimize of investment cost. In the current research, chemical method will be used to answer the problem through the addition chemical substances to the solution which often be called as inhibitor<sup>5</sup>. The inhibitor was chosen based on any consideration, i.e. : i). The chemical substance must be save material, not toxicity, not harvest the environment, construction and human. ii). It must be had capability to inhibit scale growth in some way for example through thermodynamically or physically. Two chemical substances that match to the criteria are formic acid and oxalic acid which have been known as organic material, save for the human.

The use of chemical substance was assessed through the calculation Blockage rate as equation  $t = ( Y\% ) ( \pi / 4 D_0^2 L ) / ( \rho_f / W )$ . Here, t is time for blockage rate; Y% is percentage of blockage; W is mass of scale; D<sub>0</sub> is initial inner diameter; ρ<sub>f</sub> is scale density; L is pipe length.

## 2. Methods

### A. Material

CaCO<sub>3</sub> scale in STHE module was carried out experimentally by mixing the solution of CaCl<sub>2</sub> and Na<sub>2</sub>CO<sub>3</sub> which made by powder that supplied by Merck® to guarantee its purity. Demineralized water which supplied by PT. Brataco Indonesia was used as the solvent. The reaction of those two materials were supposed that occurred according to the reaction such as shown in equation  $CaCl_{2(aq)} + Na_2CO_{3(aq)} \rightarrow CaCO_{3(s)} + 2NaCl_{(aq)}$ . Concentration of calcium was determined as 3.500 and sodium solution was set in its stoichiometry. The solution was subsequently filtrated two times by 0.22 μm micropore® paper to waste dirty material.

### B. Experimental design

Inhibitor was defined as independent variable either otherwise concentration of calcium; solution temperature and flow rate was functioned as fixed variable. Calcium concentration was set at 3,500 ppm; inhibitor concentration was set at 5,00 and 10.00 ppm; inlet temperature of STHE was set at 60 °C and flow rate at 30.00 ml/min. Scale deposited was defined as dependent variable either of blank and antiscalant experiment. Cold water that was needed to absorb the heat was inserted in the STHE module at 30 °C either for linear flow and cross flow, both at the flow rate 60 ml/min. Temperature of cold and hot water that left the module was also measured and stand as dependent variables.

### C. Experimental process

Experimental process was schematically illustrated in Fig.1. Vessel (1) contained solution of CaCl<sub>2</sub>.2H<sub>2</sub>O and vessel (2) contained solution of Na<sub>2</sub>CO<sub>3</sub>. An electrical heater was employed in each vessel (3) to control solution temperature automatically at the value needed and helped by a sensor (4) under computerized program control (7). To provide the solution in homogeneous either in temperature and chemical substance, a stirrer (5) was employed and set at 30 rpm automatically by computer program. Solution in vessel (1) and (2) was pumped by dosing pump CHEM FEED Ca-92683 (6) similarly in flowrate 30.00 mL/min and was met in STHE module (10). Ground water in cool water tank (12) was pumped by pump (13) to the module. Temperature at point (8), (9) and (11) was acquisitioned by computer program.

### D. Shell and Tube Heat Exchanger Module

STHE module was employed to conduct the experiment which fouling process was investigated. Design STHE module was depicted in Fig.2. Pipe length was determined 250 mm and

its inner diameter in 16 mm. The pipe made of copper which commercially sold in the market. Nomenclature of  $D_o$ ;  $D_f$ ;  $k_f$ ;  $\rho_f$ ; and  $L$  are obviously described that needed when substituted the parameter to the equation (1) and (2).

Rubber seal was mounted at the end of pipe to avoid the leakage. Temperature of inlet and outlet either for cold and hot water was measured and recorded in computer program. The direction of cold water flow could be replaced from right to left to provide even cross flow or linear flow model. Outside cover at two ends of pipe could be released which was done when dryer processing; mass collecting and pipe cleaning.

### **3. Results and Discussion**

#### **A. Deposition**

Deposition of scale mass either of blank and antiscalant sample are listed in Table 1 after dryer processing was done in 60 °C for six hours duration. In the current research the data shows that the deposition of STHE in linear flow less than the deposition of cross flow model. It could be caused by the heat absorption in the first shell by cold water of linear model of STHE was better than cross flow model.

The table also shows that scale deposition of blank experiment has higher magnitude and the experiment in the presence of formic acid 10.00 ppm is fewer. This would be the evident that formic acid has better performance to inhibit  $\text{CaCO}_3$  fouling than oxalic acid.

#### **B. X- Ray Diffraction Analysis and Cristal Phase Distribution**

Crystal distribution was quantificated through Rietveld refinery method, supported by FullProf program version 2.0 and confirmed by ICDD-PDF number 00-005-0586; 00-041-1475; 01-072-0506 for calcite, aragonite and vaterite. The results of the quantification were listed in Table 2 and was used to calculate average crystal density ( $\rho_f$ ) and average thermal conductivity ( $k_f$ ) of all experiment. Calculation average fouling density was done through equation  $\rho_f = \rho_{vat} \cdot \% \text{Vat} + \rho_{ar} \cdot \% \text{Ar} + \rho_{cal} \cdot \% \text{Cal}$ . Here,  $\rho_{vat}$ ;  $\rho_{ar}$ ;  $\rho_{cal}$  is the density of vaterite; aragonite and calcite respectively.  $\% \text{Vat}$ ;  $\% \text{Ar}$  and  $\% \text{Cal}$  is the percentage of crystal phases that had been quantificated through Rietveld method. Abbreviation LF in the table represent the experiment was operated as Linear Flow otherwise CF was Cross Flow model.

#### **C. Blockage Rate**

Calculation of the pipe blockage rate is used to predict the condition of the pipe in relation to determining the treatment or cleaning of the crust from within the pipeline on a time line

maintenance basis. In experiments without using pipe additives it will be completely blocked within 600 hours for experiments with the Linear Flow model. For experiments using 10 ppm formic acid additives, the pipe will be completely blocked after 854 hours of operation for longer by 42.3%. While experiments with oxalic acid showed the results of the pipe will be completely blocked after the operation for 717 hours to 19.5% longer. Thus, the rate of pipe blockage with the use of formic acid is lower or longer is completely blocked compared with oxalic acid.

#### 4. Conclusion

Blockage rate in the pipe of STHE operated as linear and cross flow model has been investigated. STHE operated as linear flow produced fewer fouling resistance than cross flow. The use formic acid as inhibitor is successfully declined blockage rate than oxalic acid.

#### Acknowledgement

The author would like to thank to the staff of Laboratory of Metrology and Instrumentation, Industrial Technology Department, School of Vocation, Diponegoro University.

#### References

1. M. Jamialahmadi and H. M. Steinhagen, *Chem Eng Res Des*, 85 (2007)
2. Z. Belarbi, J. Gambya, L. Makhloufi, B. Sotta, B. Tribollet, *J Cryst Growth*, 386 (2014)
3. A. Martinoda, M. Euvrard, A. Foissy, A. Neville, *Desalination*, 220 (2008)
4. M. G. Mwaba, G. Junjie, G. Mohammad, *J Cryst Growth*, 303 (2007)
5. K. Labioda and S. Ghizellaoui, *Energy Procedia*, 18 (2012)
6. N. N. Al-Mutairi, F. Aleem, M. I. Al-Ahmad, *Des and Wt Treat*, 10 (2009)

#### Figure Caption :

**Fig. 1.** Build inhouse experimental rig

**Fig. 2.** Shell and Tube Heat Exchanger module






Fig. 1 W. Mangestiyono, et al




Fig. 2 W. Mangestiyono, et al

**Table Caption :**

**Table 1.** Deposition of every experiment

**Table 2.** Crystals phases quantification of all experiment

**Table 3.** Average fouling density and thermal conductivity of all experiment

Table 1. W. Mangestiyono, et al

No	Experiment	Deposition (gr)
1	Blank sample, LF	0.9243
2	Blank sample, CF	0.9646
3	Formic acid 5.00 ppm, LF	0.7245
4	Formic acid 10.00 ppm, LF	0,6486
5	Oxalic acid 5.00 ppm, LF	0.8164
6	Oxalic acid 10.00 ppm, LF	0.7672

Table 2. W. Mangestiyono, et al

No.	Eksperimen	Persentase fase (%)		
		Vaterit	Aragonit	Kalsit
1.	Tanpa aditif, LF	32	31	37
2.	Asam Format 5 ppm, LF	45	32	23
3.	Asam format 10 ppm, LF	50	35	15
4.	Asam oksalat 5 ppm, LF	34	28	38
5.	Asam oksalat 10 ppm, LF	37	23	40

Table 3. W. Mangestiyono, et al

No.	Eksperimen	Prediksi Laju Penyumbatan (Kg/Total Jam)			
		Tersumbat 25%	Tersumbat 50%	Tersumbat 75%	Tersumbat 100%
1.	Tanpa aditif, LF	0.035/ 150	0.069/ 300	0.104/ 450	0.139/ 600
2.	Asam format 5 ppm, LF	0.044/ 191	0.088/ 382	0.132/ 572	0.176/ 763
3.	Asam format 10 ppm, LF	0.049/ 213	0.099/ 427	0.148/ 640	0.197/ 854
4.	Asam oksalat 5 ppm, LF	0.039/ 169	0.078/ 338	0.117/ 508	0.156/ 677
5.	Asam oksalat 10 ppm, LF	0.041/ 179	0.083/ 358	0.124/ 537	0.166/ 717