

Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

by Stalis Norma Ethica

Submission date: 03-Aug-2020 03:46PM (UTC+0700)

Submission ID: 1365437433

File name: 2020_Current_Application_Mini-review.docx (92.18K)

Word count: 2240

Character count: 14795



Mini Review

Copyright © All rights are reserved by Stalis

Norma Ethica

Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

Stalis Norma Ethica^{1*}, Akbar Firmansyah², Sakti Imam Muchlissin³, Ayu Rahmawati Sulistyningtyas⁴, Aditya Rahman Ernanto⁵, Ragil Saptaningtyas⁵, RM Bagus Irawan Widyawardhana⁶ and Sri Darmawati⁷

¹Magister of Medical Laboratory Science Study Program, Universitas Muhammadiyah Semarang, Indonesia

²Department of Fisheries and Marine Sciences, Diponegoro University, Indonesia

³Department of Fisheries and Marine Sciences, Diponegoro University, Indonesia

⁴Diploma 3 of Medical Laboratory Technology Study Program, Universitas Muhammadiyah Semarang, Indonesia

⁵Diploma 4 of Medical Laboratory Technology Study Program, Universitas Muhammadiyah Semarang, Indonesia

⁶Diploma 3 of Medical Laboratory Technology Study Program, Universitas Muhammadiyah Semarang, Indonesia

⁷Mechanical Engineering Study Program, Universitas Muhammadiyah Semarang, Indonesia

⁸Magister of Medical Laboratory Science Study Program, Universitas Muhammadiyah Semarang, Indonesia

*Corresponding author: Stalis Norma Ethica, Magister of Medical Laboratory Science Study Program, Universitas Muhammadiyah Semarang, Indonesia.

Received Date: February 10, 2020

Published Date: February 28, 2020

Abstract

Major challenges in global groundwater supply mainly come from population growth and climate change requiring innovative water technologies to keep steady supply of drinking water and decrease water pollution worldwide. In particular, agricultural activities impact groundwater pollution. Against this background, the adaptation of highly advanced bioremediation supported by microencapsulation technology to traditional process engineering offers new opportunities in technological developments for advanced groundwater and wastewater technology processes. In this study, benefits of microencapsulation technology for in situ bioremediation of polluted groundwater applications, particularly in bio-augmentation and bio-stimulation, are presented. In addition, an overview of recent advances in microencapsulation technology for contaminated groundwater treatment processes is provided, including the use of various micro-carrier materials are also summarized.

Keywords: Microencapsulation; Groundwater contamination; Micro-carrier; Bioremediation

Introduction

The long-term establishment of the global water supply and sustainability is closely related with the world population growth and global climate change. Steadfast growth of the world's population forecasted to be almost multiplied by two from 3.4 to 6.3 billion between 2009 - 2050, is presented by a predicted required growth of 70% agriculture production by 2050 [1]. Hence, the need for fresh water is dramatically increasing, especially for food production. It is because 70% of the withdrawals of world's freshwater are already adjudged for agricultural land irrigation. Today each year, 64 billion cubic meters of fresh water are consumed progressively by world's population [2].

In developing countries, ground water contamination is a key issue, with high levels of pollutants being reported in various regions. Various contamination control and groundwater treatment technologies methods should be applied to overcome this problem [3]. Groundwater treatment technologies encompass physical, chemical, or biological treatment techniques. They could be divided as ex-situ or in-situ technologies.

Aside of world population growth and global climate change, in particular, agricultural activities have been known to give impact to groundwater pollution. For example, high nitrogen



fertilizers application rates have been associated with the raise of groundwater pollution [4]. Groundwater has been found as vulnerable to pesticides used in agricultural land [5].

Public concern with polluted soil and groundwater encouraged the development of programs designed to control and remediate this contamination, as well as to prevent further contamination [1]. Bioremediation as an environmentally friendly, socially allowable and economically viable is among the best way to eliminate pollutants from the environment. In bioremediation, microorganisms with beneficial biological activity, including fungi, algae, bacteria, and yeast, could be utilized in their naturally occurring forms [6].

In situ bioremediation involving bio-stimulation and/ or bio-augmentation, being an economical and eco-friendly approach, has come out as the most beneficial soil and water clean-up technique for contaminated sites [7]. Systems involving degrading bacteria have been found helpful in supporting bioremediation option to treat the polluted groundwater [8]. Cells of degrading bacteria have been known as bioremediation agent [9]. Microencapsulation is among important strategy used in bio-augmentation and bio-stimulation improve the effectiveness of bioremediation processes [10].

Microencapsulation is among quality preservation techniques of vulnerable substances, such as enzymes, living bacterial cells, phytochemicals, and a method for generation of materials with novel precious characteristics. Microencapsulation is defined as a process of packing micron-sized particles in a polymeric shell. Various techniques are now available for the encapsulation of different entities. This mini review provides a literature review of different microencapsulation techniques applied in bioremediation of groundwater worldwide in the last ten years [1].

Discussion

Bioremediation for polluted groundwater

With latest advancements, bioremediation offers an environmentally friendly, socially acceptable and economically viable as well as choice option to deplete pollutants from the environment. There are three major ways of bioremediation including the use of microorganisms, plants and enzymes as remediation agent [11].

Bioremediation technology optimizes and exploits the natural role of microorganisms in the transformation and mineralization of these environmental pollutants. The range of contaminated environments may include surface and subsurface soils and surface and groundwater. Bioremediation for contaminated sites including groundwater containing heavy metals and/or organic pollutants usually involves bio-augmentation and/or bio-stimulation [10]. Bio-augmentation could be defined as addition of pre-grown microbial cultures to support the degradation of unwanted substances (contaminants), while bio-stimulation is the injection of nutrients and other supplementary substances to the indigenous microbial

population to influence propagation at a stimulated rate [7].

As the concern towards environmental deterioration grows worldwide, new technological achievements become important for all countries. Among the technologies offering great potential of bioremediation is the microencapsulation of active material including living cells or microorganisms [12]. For bioremediation to be effective, microorganisms must enzymatically attack the pollutants and convert them to harmless products [11].

Role of microencapsulation in bioremediation

Microencapsulation is defined as a process of enclosing or encapsulating micron-sized particles of solids or small drops of liquids or gasses in an inert shell, which in turn protects and isolates them from the external environment [13]. Micro-particles are products obtained by microencapsulation. When the particles have diameter between 3–800nm, they are regarded as micro-particles, microspheres or microcapsules. Micro-capsules are distinguished from microspheres in terms of morphology and internal structure [14].

Microencapsulation is a technology developed to pack solids, liquids and gases in tiny, sealed capsules isolating and protecting them from harsh environmental factors, such as moisture, light, oxygen, and interaction with other substances. Such microcapsules could gradually release their contents under specific conditions at controlled rates. Those packs are spherical with a micrometer size; yet are highly affected by the structure of micro-carriers and the core components [15,16].

Degradation activities naturally mediated by microorganisms used as bioremediation agent could detoxify pollutants. It is also the goal bioremediation to develop reliable technology, which can accelerate this degradation process, to reduce health risks of the pollutants and to restore the affected site into its natural state. However, even though these organisms have high degradation performance, there are limitations in success including microbial inoculum distribution and handling, suppression by parasites and predators as well as nutrient limitation [17]. These factors highly affect microbial bioremediation agent to survive in the environment. To overcome the issues, possible strategies include improved delivery system of microbial inoculum on microencapsulation technology, which could provide protection through the making of micro-environments and allow controlled release of inoculum to the targeted site [18].

Bio-stimulation supported by microencapsulation

Bio-stimulation is a commonly used technique for bioremediation involving the addition of rate-limiting nutrients to speed up the biodegradation process. Bio-stimulation often includes the addition of oxygen and nutrients to aid indigenous microorganisms as bioremediation agent. The nutrients are essential as the basic building blocks of life allowing the microorganisms to produce particular enzymes, which could degrade pollutants [11].

A number of studies have reported the use of controlled release of active materials as a way of bio-stimulation and providing the nutrients required or essential for the bioremediation process [12]. In this sense, bio-stimulation could be highly supported by microencapsulation. The use of microencapsulated microorganisms offers a great potential in degrading pollutants through bioremediation. Microencapsulation of living microbial cells in a semi-permeable gel or carrier materials bring more advantages over the free cell bio-augmentation. The microencapsulation could prevent microbial cells from bacteriophage infections and protozoa grazing. It supports both biological and physical stabilities, by decreasing risks such as brief and sudden variations of pH or temperature; covers from abiotic stresses coming from heavy metals or other toxic compounds [19]. In addition, microencapsulation using carboxymethyl-cellulose as micro-carrier could form fine structures for nutrient release, producing bio-stimulation in biodegradation process [12]. Thus, in general, microencapsulation is beneficial in enhancing cell survival and high biomass concentration

Bio-augmentation supported by microencapsulation

Bioremediation of pollutants or contaminants by utilizing microorganisms is among the most important strategies to eliminate contaminants from groundwater. However, there are limitations of this approach since many contaminants are not efficiently removed [11]. To overcome these limitations, bio-augmentation also includes addition more specific and efficient pollutant-biodegrading microorganisms into a microbial community as a way to support the ability of this microbial community to biodegrade contaminants. In this aspect, microencapsulation of the pollutant-

biodegrading microbial cells is relevant to allow steady supply of the bioremediation agent.

To date, the elimination of contaminants by bio-augmentation has been widely investigated in surface water, soil and groundwater [19]. However, although it has been practiced in agriculture and in wastewater treatment for years, bio-augmentation is still experimental. Many factors (e.g. predation, competition or sorption) conspire against it. However, a number of strategies have been explored to make bio-augmentation a beneficial technology in sites lacking significant populations of biodegrading microorganisms. The pollutant degradation rate under optimal local conditions, may increase upon addition of an inoculant to remediate a chemical spill; yet, the most successful examples of bio-augmentation occur in confined systems, such as bioreactors allowing controlled conditions to favor prolonged activity and survival of the exogenous microbial population [20].

Micro-carriers used in groundwater bioremediation applications

One of the vital steps in micro-coating is choosing the most suitable wall materials/ micro-carriers. Micro-carriers or coating materials usually are film-forming materials opted from various natural and synthetic polymers, or combination of both, depending on the inner component and the overall desired microcapsule characteristics [15,21]. Ideally, the wall or sphere material should be an emulsifier, so it could promote enough content release when reconstructed into the product, have a low viscosity due to high concentrations of solids, have good film-forming performance, and have high hygroscopicity.

Table 1: Reported studies related with the application of microencapsulation technology for bioremediation of polluted groundwater in the last decade (2010-2020).

Pollutant	Encapsulated Microorganism	Micro-Carrier	Country	Author
Atrazine	<i>Pseudomonas sp.</i>	Polyethylene oxide; polycaprolactone, polyethylene glycol	Israel	Klein et al., 2012
Xylene	<i>Streptomyces sp.</i>	Sodium alginate	Algeria	Chiki et al., 2015
Hydrocarbon	<i>Bacillus subtilis</i>	Chitosan	Brazil	Dellagnezze et al., 2016
Cr(III)	<i>Lysinibacillus fusiformis</i>	Arabic gum and sorbitol	China	Huang et al., 2016
Dichlobenil herbicide	<i>Aminobacter sp.</i>	Trehalose	Denmark	Schultz Jensen et al., 2016
Trichloroethylene (TCE)	<i>Pseudomonas putida</i> ; <i>Dehalococcoides sp.</i>	Zero-valent iron (ZVI)	USA	Shanhogue et al., 2017
Phenol	<i>Pseudomonas sp.</i> ,	Gellan gum	Malaysia	Aisami, 2017
	<i>Alcaligenes sp.</i> ,			
	<i>Serratia sp.</i>			
Cr(VI)	<i>Morganella morganii</i>	Polystyrene; polysulfone	Turkey	Sarioglu, et al., 2017
1,4-dioxane; chlorinated aliphatic hydrocarbons	<i>Rhodococcus rhodochrous</i>	Alginate; gellan gum	USA	Rasmussen 2018

Acetochlor herbicides	<i>Sphingomonas sp.</i>	No micro-carrier, dried cells	China	Wang et al., 2018
Trichloroethylene (TCE)	<i>Lactobacillus casei</i> ,	Polyvinyl alcohol (PVA); sodium alginate (SA)	USA	Nutter et al., 2019
	<i>L. acidophilus</i>			
Trichloroethene	<i>Clostridium butyricum</i>	Silica gel	Taiwan	Lo et al., 2020
Carbazole	<i>Thalassospira profundimaris</i>	Gellan gum	Malaysia	Manas et al., 2020

Over the past 10 years, the number of publications on the use of encapsulated microorganisms for the elimination of pollutants in contaminated groundwater has been increasing steadily. The following are among the most commonly used wall/ sphere materials in microencapsulation: carbohydrates (sucrose, starch, maltodextrins, and cyclodextrins), cellulose (carboxymethyl cellulose and its derivatives), gum (Arabic and agar), lipids (wax and fatty acids), and proteins (gelatin, gluten, and casein) [16,21]. Most of these materials have been used in the bioremediation of groundwater in the last decade as listed in Table 1.

Based on Table 1, in the last decade, microencapsulation technology has been widely applied in bioremediation of groundwater polluted by various substances including hydrocarbons, heavy metal, dioxin, herbicides, and plastics. Various micro-carriers grouped as alginates, gums, polymers have also been used as encapsulating materials providing protection as well as nutrition source in suitable environment allowing the release and growth of microbial cells. Interestingly, the microbial cell immobilization could be done by creation of dried cells, which means it does not necessarily need any micro-carrier [8].

Based on this literature review, microencapsulation technologies with various applied micro-carriers as single or combinations keep producing novel micro-engineered materials offering great potential for more innovations in the future. Such innovations are in particular very beneficial for the treatment for contaminated groundwater [22-29].

Conclusion

There is a need for novel advanced groundwater bioremediation technologies, in particular to ensure a high quality of drinking water and to eliminate water pollutants using suitable treatment systems. Micro-engineered materials produced by microencapsulation technology offer the potential for novel water technologies that can be easily adapted to groundwater bioremediation applications. To date, microencapsulation with various micro-carriers keep producing novel micro-engineered materials offering great potential for more innovations in the coming decades, in particular for treating heavily degradable contaminants in groundwater.

Acknowledgment

This study is part of work dedicated to Program Hibah Penelitian Terapan (PT) 2020 funded by Kementerian Riset dan Teknologi/ Badan Riset Dan Inovasi Nasional (RISTEK BRIN) or Ministry of Research and Technology of Indonesia.

Conflict of Interest

No conflict of interest.

Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

ORIGINALITY REPORT

16%

SIMILARITY INDEX

2%

INTERNET SOURCES

14%

PUBLICATIONS

6%

STUDENT PAPERS

PRIMARY SOURCES

- 1** Marcela Claudia Pagano, Neimar Freitas Duarte, Eduardo José Azevedo Corrêa. "Effect of crop and grassland management on mycorrhizal fungi and soil aggregation", *Applied Soil Ecology*, 2020
Publication 1%

- 2** Ratna G. Suthar, Bin Gao. "Nanotechnology for drinking water purification", Elsevier BV, 2017
Publication 1%

- 3** Marianna Mamusa, Constantina Sofroniou, Claudio Resta, Sergio Murgia, Emiliano Fratini, Johan Smets, Piero Baglioni. "Tuning the Encapsulation of Simple Fragrances with an Amphiphilic Graft Copolymer", *ACS Applied Materials & Interfaces*, 2020
Publication 1%

- 4** Sergio Sánchez, Betty Olson. "Ecology and industrial microbiology", *Current Opinion in Microbiology*, 2005
Publication 1%

5

Kai Betlem, Amanpreet Kaur, Alexander D. Hudson, Robert D. Crapnell et al. " Heat-Transfer Method: A Thermal Analysis Technique for the Real-Time Monitoring of Growth in Buffered Solutions and Digestate Samples ", ACS Applied Bio Materials, 2019

Publication

1%

6

M.L. Brusseau. "Soil and Groundwater Remediation", Elsevier BV, 2019

Publication

1%

7

Min Wu, Björn Johannesson, Mette Geiker. "A review: Self-healing in cementitious materials and engineered cementitious composite as a self-healing material", Construction and Building Materials, 2012

Publication

1%

8

[recent-science.com](https://www.recent-science.com)

Internet Source

1%

9

M Prihaswati, V D Mawarsari, E Winaryati. "Applying google classroom based on prospective teacher", Journal of Physics: Conference Series, 2020

Publication

1%

10

Alessandra Scardigno. "New solutions to reduce water and energy consumption in crop production: A water–energy–food nexus perspective", Current Opinion in Environmental

1%

Science & Health, 2020

Publication

11 Jean-Marc Bollag, Tawna Mertz, Lewis Otjen. "Role of Microorganisms in Soil Bioremediation", American Chemical Society (ACS), 1994 1%

Publication

12 Submitted to EDMC 1%
Student Paper

13 Submitted to University of New South Wales 1%
Student Paper

14 sinta3.ristekdikti.go.id 1%
Internet Source

15 ccsenet.org <1%
Internet Source

16 Submitted to Universitas Diponegoro <1%
Student Paper

17 biocoreopen.org <1%
Internet Source

18 Idiani Darmawati, Aulia Rahmah, Zulkhah Noor. "The influence of mackerel fish (*Rastrelliger* sp.) consumption towards the number of pyramidal cell in cerebral cortex of congenital hypothyroid rats (*Rattus norvegicus*)", AIP Publishing, 2018 <1%
Publication

19 Cipto, K A Rahangmetan, F Sariman, Hariyanto,

S B Bahar, M T Sapsal. "Stress analysis on the frame of peanut skin peeler using autodesk inventor software", IOP Conference Series: Earth and Environmental Science, 2019

Publication

<1%

Exclude quotes Off

Exclude matches Off

Exclude bibliography Off