

# Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

*by Sri Darmawati*

---

**Submission date:** 07-Oct-2021 08:45PM (UTC+0700)

**Submission ID:** 1667746253

**File name:** WJASS.StalisNormaE.pdf (491.8K)

**Word count:** 3406

**Character count:** 21601

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/339400065>

# Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

Article · February 2020

DOI: 10.33552/WJAS.2020.04.000587

CITATIONS

0

READS

100

8 authors, including:



**Stalis Norma Ethica**  
Universitas Muhammadiyah Semarang

83 PUBLICATIONS 177 CITATIONS

[SEE PROFILE](#)



**Akbar Firmansyah**  
Politeknik Negeri Bandung

5 PUBLICATIONS 5 CITATIONS

[SEE PROFILE](#)



**Sakti Imam Muchlissin**  
Universitas Diponegoro

29 PUBLICATIONS 68 CITATIONS

[SEE PROFILE](#)



**Ayu Rahmawati Sulistyanyngtyas**  
Universitas Muhammadiyah Semarang

49 PUBLICATIONS 25 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:



Biotechnology applications: Phenotypic & genotypic characterization of food borne Bacteria [View project](#)



Evaluasi Potensi Enzim Protease Fibrinolitik dari Jaringan Teripang Pasir (*Holothuria scabra*) dan dari Bakteri pada Produk Fermentasinya sebagai Agen Antitrombosis [View project](#)



ISSN: 2641-6379

DOI: 10.33552/WJASS.2020.04.000587

World Journal of  
Agriculture and Soil Science

ris Publishers

Mini Review

Copyright © All rights are reserved by Stalis Norma Ethica

# Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

Stalis Norma Ethica<sup>1\*</sup>, Akbar Firmansyah<sup>2</sup>, Sakti Imam Muchlissin<sup>3</sup>, Ayu Rahmawati Sulistyanningtyas<sup>4</sup>, Aditya Rahman Ernanto<sup>5</sup>, Ragil Saptaningtyas<sup>5</sup>, RM Bagus Irawan Widyardhana<sup>6</sup> and Sri Darmawati<sup>7</sup>

<sup>1</sup>Magister of Medical Laboratory Science Study Program, Muhammadiyah University of Semarang, Indonesia

<sup>2</sup>Department of Fisheries and Marine Sciences, Diponegoro University, Indonesia

<sup>3</sup>Department of Fisheries and Marine Sciences, Diponegoro University, Indonesia

<sup>4</sup>Diploma 3 of Medical Laboratory Technology Study Program, Muhammadiyah University of Semarang, Indonesia

<sup>5</sup>Diploma 4 of Medical Laboratory Technology Study Program, Muhammadiyah University of Semarang, Indonesia

<sup>6</sup>Diploma 3 of Medical Laboratory Technology Study Program, Muhammadiyah University of Semarang, Indonesia

<sup>7</sup>Mechanical Engineering Study Program, Muhammadiyah University of Semarang, Indonesia

<sup>7</sup>Magister of Medical Laboratory Science Study Program, Muhammadiyah University of Semarang, Indonesia

\*Corresponding author: Stalis Norma Ethica, Magister of Medical Laboratory Science Study Program, Muhammadiyah University of Semarang, Indonesia.

Received Date: February 10, 2020

Published Date: February 13, 2020

## Abstract

Major challenges in global groundwater supply mainly comes from population growth and climate change requiring innovative water technologies to keep steady supply of drinking water and decrease water pollution worldwide. In particular, agricultural activities impact groundwater pollution. Against this background, the adaptation of highly advanced bioremediation supported by microencapsulation technology to traditional process engineering offers new opportunities in technological developments for advanced groundwater and wastewater technology processes. In this study, benefits of microencapsulation technology for in situ bioremediation of polluted groundwater applications, particularly in bio-augmentation and bio-stimulation, are presented. In addition, an overview of recent advances in microencapsulation technology for contaminated groundwater treatment processes is provided, including the use of various micro-carrier materials are also summarized.

**Keywords:** Microencapsulation; Groundwater contamination; Micro-carrier; Bioremediation

## Introduction

The long-term establishment of the global water supply and sustainability is closely related with the world population growth and global climate change. Steadfast growth of the world's population forecasted to be almost multiplied by two from 3.4 to 6.3 billion between 2009 - 2050, is presented by a predicted required growth of 70% agriculture production by 2050 [1]. Hence, the need for fresh water is dramatically increasing, especially for food production. It is because 70% of the withdrawals of world's freshwater are already adjudged for agricultural land irrigation. Today each year, 64 billion cubic meters of fresh water are consumed progressively by worlds' population [2].

In developing countries, ground water contamination is a key issue, with high levels of pollutants being reported in various regions. Various contamination control and groundwater treatment technologies methods should be applied to overcome this problem [3]. Groundwater treatment technologies encompass physical, chemical, or biological treatment techniques. They could be divided as ex-situ or in-situ technologies.

Aside of world population growth and global climate change, in particular, agricultural activities have been known to give impact to groundwater pollution. For example, high nitrogen



fertilizers application rates have been associated with the raise of groundwater pollution [4]. Groundwater has been found as vulnerable to pesticides used in agricultural land [5].

Public concern with polluted soil and groundwater encouraged the development of programs designed to control and remediate this contamination, as well as to prevent further contamination [1]. Bioremediation as an environmentally friendly, socially allowable and economically viable is among the best way to eliminate pollutants from the environment. In bioremediation, microorganisms with beneficial biological activity, including fungi, algae, bacteria, and yeast, could be utilized in their naturally occurring forms [6].

In situ bioremediation involving bio-stimulation and/ or bio-augmentation, being an economical and eco-friendly approach, has come out as the most beneficial soil and water clean-up technique for contaminated sites [7]. Systems involving degrading bacteria have been found helpful in supporting bioremediation option to treat the polluted groundwater [8]. Cells of degrading bacteria have been known as bioremediation agent [9]. Microencapsulation is among important strategy used in bio-augmentation and bio-stimulation improve the effectiveness of bioremediation processes [10].

Microencapsulation is among quality preservation techniques of vulnerable substances, such as enzymes, living bacterial cells, phytochemicals, and a method for generation of materials with novel precious characteristics. Microencapsulation is defined as a process of packing micron-sized particles in a polymeric shell. Various techniques are now available for the encapsulation of different entities. This mini review provides a literature review of different microencapsulation techniques applied in bioremediation of groundwater worldwide in the last ten years [1].

## Discussion

### Bioremediation for polluted groundwater

With latest advancements, bioremediation offers an environmentally friendly, socially acceptable and economically viable as well as choice option to deplete pollutants from the environment. There are three major ways of bioremediation including the use of microorganisms, plants and enzymes as remediation agent [11].

Bioremediation technology optimizes and exploits the natural role of microorganisms in the transformation and mineralization of these environmental pollutants. The range of contaminated environments may include surface and subsurface soils and surface and groundwater. Bioremediation for contaminated sites including groundwater containing heavy metals and/or organic pollutants usually involves bio-augmentation and/or bio-stimulation [10]. Bio-augmentation could be defined as addition of pre-grown microbial cultures to support the degradation of unwanted substances (contaminants), while bio-stimulation is the injection of nutrients and other supplementary substances to the indigenous microbial

population to influence propagation at a stimulated rate [7].

As the concern towards environmental deterioration grows worldwide, new technological achievements become important for all countries. Among the technologies offering great potential of bioremediation is the microencapsulation of active material including living cells or microorganisms [12]. For bioremediation to be effective, microorganisms must enzymatically attack the pollutants and convert them to harmless products [11].

### Role of microencapsulation in bioremediation

Microencapsulation is defined as a process of enclosing or encapsulating micron-sized particles of solids or small drops of liquids or gasses in an inert shell, which in turn protects and isolates them from the external environment [13]. Micro-particles are products obtained by microencapsulation. When the particles have diameter between 3–800nm, they are regarded as micro-particles, microspheres or microcapsules. Micro-capsules are distinguished from microspheres in terms of morphology and internal structure [14].

Microencapsulation is a technology developed to pack solids, liquids and gases in tiny, sealed capsules isolating and protecting them from harsh environmental factors, such as moisture, light, oxygen, and interaction with other substances. Such microcapsules could gradually release their contents under specific conditions at controlled rates. Those packs are spherical with a micrometer size; yet are highly affected by the structure of micro-carriers and the core components [15,16].

Degradation activities naturally mediated by microorganisms used as bioremediation agent could detoxify pollutants. It is also the goal bioremediation to develop reliable technology, which can accelerate this degradation process, to reduce health risks of the pollutants and to restore the affected site into its natural state. However, even though these organisms have high degradation performance, there are limitations in success including microbial inoculum distribution and handling, suppression by parasites and predators as well as nutrient limitation [17]. These factors highly affect microbial bioremediation agent to survive in the environment. To overcome the issues, possible strategies include improved delivery system of microbial inoculum on microencapsulation technology, which could provide protection through the making of micro-environments and allow controlled release of inoculum to the targeted site [18].

### Bio-stimulation supported by microencapsulation

Bio-stimulation is a commonly used technique for bioremediation involving the addition of rate-limiting nutrients to speed up the biodegradation process. Bio-stimulation often includes the addition of oxygen and nutrients to aid indigenous microorganisms used as bioremediation agent. The nutrients are essential as the basic building blocks of life allowing the microorganisms to produce particular enzymes, which could degrade pollutants [11].

14

A number of studies have reported the use of controlled release of active materials as a way of bio-stimulation and providing the nutrients required or essential for the bioremediation process [12]. In this sense, bio-stimulation could be highly supported by microencapsulation. The use of microencapsulated microorganisms offers a great potential in degrading pollutants through bioremediation. Microencapsulation of living microbial cells in a semi-permeable gel or carrier materials bring more advantages over the free cell bio-augmentation. The microencapsulation could prevent microbial cells from bacteriophage infections and protozoa grazing. It supports both biological and physical stabilities, by decreasing risks such as brief and sudden variations of pH or temperature; covers from abiotic stresses coming from heavy metals or other toxic compounds [19]. In addition, microencapsulation using carboxymethyl-cellulose as micro-carrier could form fine structures for nutrient release, producing bio-stimulation in biodegradation process [12]. Thus, in general, microencapsulation is beneficial in enhancing cell survival and high biomass concentration

### Bio-augmentation supported by microencapsulation

Bioremediation of pollutants or contaminants by utilizing microorganisms is among the most important strategies to eliminate contaminants from groundwater. However, there are limitations of this approach since many contaminants are not efficiently removed [11]. To overcome these limitations, bio-augmentation also includes addition more specific and efficient pollutant-biodegrading microorganisms into a microbial community as a way to support the ability of this microbial community to biodegrade contaminants. In this aspect, microencapsulation of the pollutant-

biodegrading microbial cells is relevant to allow steady supply of the bioremediation agent.

To date, the elimination of contaminants by bio-augmentation has been widely investigated in surface water, soil and groundwater [19]. However, although it has been practiced in agriculture and in wastewater treatment for years, bio-augmentation is still experimental. Many factors (e.g. predation, competition or sorption) conspire against it. However, a number of strategies have been explored to make bio-augmentation a beneficial technology in sites lacking significant populations of biodegrading microorganisms. The pollutant degradation rate under optimal local conditions, may increase upon addition of an inoculant to remediate a chemical spill; yet, the most successful examples of bio-augmentation occur in confined systems, such as bioreactors allowing controlled conditions to favor prolonged activity and survival of the exogenous microbial population [20].

### Micro-carriers used in groundwater bioremediation applications

One of the vital steps in micro-coating is choosing the most suitable wall materials/ micro-carriers. Micro-carriers or coating materials usually are film-forming materials opted from various natural and synthetic polymers, or combination of both, depending on the inner component and the overall desired microcapsule characteristics [15,21]. Ideally, the wall or sphere material should be an emulsifier, so it could promote enough content release when reconstructed into the product, have a low viscosity due to high concentrations of solids, have good film-forming performance, and have high hygroscopicity.

**Table 1:** Reported studies related with the application of microencapsulation technology for bioremediation of polluted groundwater in the last decade (2010-2020).

Pollutant	Encapsulated Microorganism	Micro-Carrier	Country	Author
Atrazine	<i>Pseudomonas sp.</i>	Polyethylene oxide; polycaprolactone, polyethylene glycol	Israel	Klein et al., 2012
Xylene	<i>Streptomyces sp.</i>	Sodium alginate	Algeria	Chiki et al., 2015
Hydrocarbon	<i>Bacillus subtilis</i>	Chitosan	Brazil	[24]
Cr(III)	<i>Lysinibacillus fusiformis</i>	Arabic gum and sorbitol	China	Huang et al., 2016
Dichlobenil herbicide	<i>Aminobacter sp.</i>	Trehalose	Denmark	[28]
Trichloroethylene (TCE)	<i>Pseudomonas putida</i> ; <i>Dehalococcoides sp.</i>	Zero-valent iron (ZVI)	USA	[29]
Phenol	<i>Pseudomonas sp.</i>	Gellan gum	Malaysia	Aisami, 2017
	<i>Alcaligenes sp.</i>			
	<i>Serratia sp.</i>			
Cr(VI)	<i>Morganella morganii</i>	Polystyrene; polysulfone	Turkey	[29]
1,4-dioxane; chlorinated aliphatic hydrocarbons	<i>Rhodococcus rhodochrous</i>	Alginate; gellan gum	USA	[27]

Acetochlor herbicides	<i>Sphingomonas sp.</i>	No micro-carrier, dried cells	China	[8]
Trichloroethylene (TCE)	<i>Lactobacillus casei</i> ,	Polyvinyl alcohol (PVA); sodium alginate (SA)	USA	[26]
	<i>L. acidophilus</i>			
Trichloroethene	<i>Clostridium butyricum</i>	Silica gel	Taiwan	Lo et al., 2020
Carbazole	<i>Thalassospira profundimaris</i>	Gellan gum	Malaysia	Manas et al., 2020

Over the past 10 years, the number of publications on the use of encapsulated microorganisms for the elimination of pollutants in contaminated groundwater has been increasing steadily. The following are among the most commonly used wall/ sphere materials in microencapsulation: carbohydrates (sucrose, starch, maltodextrins, and cyclodextrins), cellulose (carboxymethyl cellulose and its derivatives), gum (Arabic and agar), lipids (wax and fatty acids), and proteins (gelatin, gluten, and casein) [16,21]. Most of these materials have been used in the bioremediation of groundwater in the last decade as listed in Table 1.

Based on Table 1, in the last decade, microencapsulation technology has been widely applied in bioremediation of groundwater polluted by various substances including hydrocarbons, heavy metal, dioxin, herbicides, and plastics. Various micro-carriers grouped as alginates, gums, polymers have also been used as encapsulating materials providing protection as well as nutrition source in suitable environment allowing the release and growth of microbial cells. Interestingly, the microbial cell immobilization could be done by creation of dried cells, which means it does not necessarily need any micro-carrier [8].

Based on this literature review, microencapsulation technologies with various applied micro-carriers as single or combinations keep producing novel micro-engineered materials offering great potential for more innovations in the future. Such innovations are in particular very beneficial for the treatment for contaminated groundwater [22-26].

## Conclusion

There is a need for novel advanced groundwater bioremediation technologies, in particular to ensure a high quality of drinking water and to eliminate water pollutants using suitable treatment systems. Micro-engineered materials produced by microencapsulation technology offer the potential for novel water technologies that can be easily adapted to groundwater bioremediation applications [27-29]. To date, microencapsulation with various micro-carriers keep producing novel micro-engineered materials offering great potential for more innovations in the coming decades, in particular for treating heavily degradable contaminants in groundwater.

## Acknowledgment

This study is part of work dedicated to Program Hibah Penelitian Terapan (PT) 2020 funded by Kementerian Riset dan Teknologi/ Badan Riset Dan Inovasi Nasional (RISTEK BRIN) or Ministry of Research and Technology of Indonesia.

## Conflict of Interest

No conflict of interest.

## References

- Bruinsma J (2009) By how much do land, water and crop yields need to increase by 2050? The resource outlook to 2050. Presented at the Food and Agriculture Organization of the United Nations Expert Meeting entitled "How to Feed the World in 2050".
- (2014) Report, WWD Managing water under uncertainty and risks.
- Massoud MA, Tarhini A, Nasr JA (2009) Decentralized approaches to wastewater treatment and management: applicability in developing countries J Environ Manage 90(1): 652-659.
- Mahvi AH, Nouri J, Babaei AA, Nabizadeh R (2005) Agricultural activities impact on groundwater nitrate pollution. International Journal of Environmental Science & Technology 2(1): 41-47.
- Saha D, Alam F (2014) Groundwater vulnerability assessment using DRASTIC and Pesticide DRASTIC models in intense agriculture area of the Gangetic plains, India. Environ Monit Assess 186(12): 8741-8763.
- Coelho LM, Rezende HC, Coelho LM, De Sousa PA, Melo DF, et al. (2015) Bioremediation of polluted waters using microorganisms. Advances in Bioremediation of Wastewater and Polluted Soil 10: 60770.
- Jyothi NV, Prasanna PM, Sakarkar SN, Prabha KS, Ramaiah PS, et al. (2010) Microencapsulation techniques, factors influencing encapsulation efficiency. J Microencapsul 27(3): 187-197.
- Saiyari DM, Chuang HP, Senoro DB, Lin TF, Whang LM, et al. (2018) A review in the current developments of genus Dehalococcoides, its consortia and kinetics for bioremediation options of contaminated groundwater. Sustainable Environment Research 28(4): 149-157.
- Ethica SN, Saptaningtyas R, Muchlissin SI, Sabdono A (2018) The development method of bioremediation of hospital biomedical waste using hydrolytic bacteria. Health and Technology 8(4): 239-254.
- Tyagi M, da Fonseca MM, de Carvalho CC (2011) Bioaugmentation and biostimulation strategies to improve the effectiveness of bioremediation processes. Biodegradation 22(2): 231-241.
- Naik MG, Duraphe MD (2012) Review paper on-Parameters affecting bioremediation. International journal of life science and pharma research 2(3): L77-L80.
- Reis EA, Rocha Leão MH, Leite SG (2013) Slow-release nutrient capsules for microorganism stimulation in oil remediation. Applied biochemistry and biotechnology 169(4): 1241-1249.
- Ghosh SK (2006) Functional coatings and microencapsulation: a general perspective. Functional coatings, pp. 1-28.
- Thies C (1996) A survey of microencapsulation processes, Simon Benita, microencapsulation and industrial applications, Ch 1. Maecel Dekker Imp. New York, USA.
- Bastos DS, Araújo KGL, Rocha Leão MH (2009) Ascorbic acid retaining using a new calcium alginate-Capsul based edible film. J Microencapsul 26(2): 97-103.
- Suave J, Dall'agnol EC, Pezzin AP T, Silva DAK, Meier MM, et al. (2006) Microencapsulation: Innovation in different areas. Health and Environment Journal 7(2): 12-20.

17. Ramirez Garcia R, Gohil N, Singh V (2019) Recent advances, challenges, and opportunities in bioremediation of hazardous materials. In *Phytomanagement of Polluted Sites*, pp. 517-568.
18. Rathore S, Desai PM, Liew CV, Chan LW, Heng PW (2013) Microencapsulation of microbial cells. *Journal of Food Engineering* 116(2): 369-381.
19. Nzila A, Razzak SA, Zhu J (2016) Bioaugmentation: An emerging strategy of industrial wastewater treatment for reuse and discharge. *Int J Environ Res Public Health* 13(9): E846.
20. El Fantroussi S, Agathos SN (2005) Is bioaugmentation a feasible strategy for pollutant removal and site remediation? *Curr Opin Microbiol* 8(3): 268-275.
21. Dubey R (2009) Microencapsulation technology and applications. *Defence Science Journal* 59(1): 82-95.
22. Bayat Z, Hassanshahian M, Cappello S (2015) Immobilization of microbes for bioremediation of crude oil polluted environments: a mini review. *Open Microbiol J* 9: 48-54.
23. Chikhi S, Ferradji FZ, Badis A, Bouzid B (2016) Microbial removal of xylene using free and immobilized *Streptomyces* sp. AB1: bioreactors application. *Desalination and Water Treatment* 57(13): 6148-6156.
24. Dellagnezze BM, Vasconcelos SP, Angelim AL, Melo VM, Santisi S, et al. (2016) Bioaugmentation strategy employing a microbial consortium immobilized in chitosan beads for oil degradation in mesocosm scale. *Mar Pollut Bull* 107(1): 107-117.
25. Meckenstock RU, Elsner M, Griebler C, Lueders T, Stumpp C, et al. (2015) Biodegradation: updating the concepts of control for microbial cleanup in contaminated aquifers. *Environ Sci Technol* 49(12): 7073-7081
26. Nutter LA, Strawn IK, White A, Hill C (2019) The Encapsulation of *Lactobacillus acidophilus* and *Lactobacillus casei* to Determine Cell Viability in a Hydrogel Biobead Matrix.
27. Rasmussen MT (2018) Co-Encapsulation of Slow Release Substrates and Microbial Cultures in Alginate and Gellan Gum Beads to Promote the Co-metabolic Transformation of 1, 4-Dioxane and Chlorinate Aliphatic Hydrocarbons.
28. Schultz Jensen N, Aamand J, Sørensen SR (2016) Bioaugmentation potential of free and formulated 2, 6-dichlorobenzamide (BAM) degrading *Aminobacter* sp. MSH1 in soil, sand and water. *AMB Express* 6(1): 33.
29. Shanbhogue SS, Bezbaruah A, Simsek S, Khan E (2017) Trichloroethene removal by separately encapsulated and co-encapsulated bacterial degraders and nanoscale zero-valent iron. *International Biodeterioration & Biodegradation* 125: 269-276.

# Current Application of Microencapsulation Technology in Bioremediation of Polluted Groundwater

## ORIGINALITY REPORT

11%

SIMILARITY INDEX

3%

INTERNET SOURCES

8%

PUBLICATIONS

4%

STUDENT PAPERS

## PRIMARY SOURCES

- 1 Parvez Iqbal, Tiejun Lu, Zhibing Zhang, Yongliang Li. "Preparation of Multilayer Microcapsules Encapsulating Aqueous Lithium Bromide and Their Mechanical Stability", Industrial & Engineering Chemistry Research, 2019  
Publication 1%
- 2 biotechgo.org  
Internet Source 1%
- 3 Submitted to Higher Education Commission Pakistan  
Student Paper 1%
- 4 Sergio Sánchez, Betty Olson. "Ecology and industrial microbiology", Current Opinion in Microbiology, 2005  
Publication 1%
- 5 Submitted to Florida Gulf Coast University  
Student Paper 1%
- 6 M.L. BRUSSEAU, R.M. MAIER. "SOIL AND GROUNDWATER REMEDIATION", Elsevier BV, 1%



2004

Publication

---

7	Submitted to University of Maryland, University College Student Paper	1 %
8	<a href="http://www.semanticscholar.org">www.semanticscholar.org</a> Internet Source	1 %
9	Submitted to University of Limpopo Student Paper	1 %
10	Jean-Marc Bollag, Tawna Mertz, Lewis Otjen. "Role of Microorganisms in Soil Bioremediation", American Chemical Society (ACS), 1994 Publication	1 %
11	Singh, Nandita, Pankaj Srivastava, Rudra Tripathi, Shubhi Srivastava, and Aradhana Vaish. "Microbial in-situ mitigation of arsenic contamination in plants and soils", Arsenic in the Environment, 2014. Publication	<1 %
12	Borrmann, Daniela, Anna Paola Trindade Rocha Pierucci, Selma Gomes Ferreira Leite, and Maria Helena Miguez da Rocha Leão. "Microencapsulation of passion fruit (Passiflora) juice with n-octenylsuccinate-derivatised starch using spray-drying", Food and Bioproducts Processing, 2013. Publication	<1 %

---

13

[www.mdpi.com](http://www.mdpi.com)

Internet Source

<1 %

---

14

"Rhizobiont in Bioremediation of Hazardous Waste", Springer Science and Business Media LLC, 2021

Publication

<1 %

---

---

Exclude quotes Off

Exclude matches Off

Exclude bibliography Off